



AUXILIARY PRODUCTS



CONSOLIDANTE PQ DUR

Water vapour permeable hardener for construction materials, water based and made of resins and polymer emulsions. **Breathable hardener.**

APPLICATIONS

- Applying CONSOLIDANTE PQ DUR on eroded substrates can prevent them from losing particles.
- Hardener primarily used for the treatment of natural stones, concrete, bricks, clay and mortars with floury surface or damage by weathering.

CHARACTERISTICS

- **Whitish liquid that turns transparent when dry. It can add a slight glow on the surface.**
- **pH >5, density 1.00 g/cm³.**
- Standard coverage 0.20 l/sqm.
- It can be applied by spray-gun, roller or paintbrush.

PACKAGING

25 litres plastic container.



CONSOLIDANTE PQ SIL

Mineralizing damp-proof hardener for construction materials, made of resins, siliceous derivatives and additives.

APPLICATIONS

- Applying CONSOLIDANTE PQ SIL on eroded substrates can prevent them from losing particles.
- Hardener primarily used for treatment of stones, concrete, bricks, clay, mortars with floury surface.
- **Its damp-proof characteristics** contributes to an excellent protection to weathering.

CHARACTERISTICS

- **Transparent liquid that turns whitish when dry.**
- **pH >13, density 1.17 g/cm³.**
- Standard coverage 0.20 l/sqm.
- It can be applied by spray-gun, roller or paintbrush.

PACKAGING

25 litres plastic container.





ELASTOMERO PQ

Waterproofing liquid made of high elastic water based elastomers, polyurethane and high elastic acrylic resins. This product becomes a waterproofing membrane after it has reticulated under ambient humidity.

APPLICATIONS

- Waterproofing layer on flat or pitched roofs, balconies and terraces, on new constructions or renovation of damaged areas.

CHARACTERISTICS

- Ultraviolet sunlight resistant.
- Transparent. It does not turn yellow.
- High superficial adherence on multiple substrates such as concrete, ceramic, wood, steel, etc.
- It can fill cracks and admits slight movements of the substrate due to its high elasticity.
- Estimated coverage of 0.30 l/sqm [variable depending on the application].

PACKAGING

20 litre plastic bucket.

MINERALIZADOR PQ

Low viscosity aqueous product based on quartz that permeates pores and capillaries of the substrate, building up insoluble quartz crystals so as to enhance the waterproofing characteristic of the treated substrate.

APPLICATIONS

- As a barrier against dampness due to capillarity inside a wall that absorbs humidity from leaks or the ground.
- As a treatment against high absorbent materials such as stone, mortars, concrete, bricks, etc.
- Hardens and consolidates porous stones, sandstones, concrete and mortar, bricks, roof tiles, etc.

SPECIFICATIONS

Type: Aqueous product
Density: 1.20 kg/dm³
Thinner: Water



PU3

Transparent waterproofing product based on modified activated aliphatic polyurethane, three-component, that improves adhesion on low absorption substrates and optimizes crosslinking.

APPLICATIONS

- Protective and sealing final layer of quartz based coating STONE VIPEQ.
- Waterproofing and protective layer on terraces, balconies and roofs.

CHARACTERISTICS

- Water vapour permeability \approx 5 g/sqm day.
- Tensile strength \geq 6,5 N/sqmm and adherence $>$ 2,5 N/sqmm.
- Providing PU3 is transparent, it can be applied on skylights, polycarbonate materials or similar.
- High adherence on most substrates.
- Compatible with high and low absorbant materials such as ceramic, granite, plastic, fibers, etc.

PACKAGING

5 litre in 3 component containers.



CHARACTERISTICS

- Transparent liquid that does not change the appearance of the treated materials.
- Permeable to water vapor.
- Improves the material resistance against freeze-thaw cycles.
- Estimated coverage between 200 and 500 g/sqm.

PACKAGING

5 or 25 litre plastic container.





LIMPIADOR VERDIN

Cleaning agent against mosses, lichens and plant waste.

APPLICATIONS

- Cleaning of substrates, roofs, façades, floors, etc. that have mosses, lichens, bacteria or algae.

CHARACTERISTICS

- Estimated coverage of 0.3 l/sqm.
- It is applied by spray-gun or roller.
- Do not apply on natural environment, wood or painted substrates or metals, because it is corrosive.
- Leave the product for at least 2 hours and then rinse thoroughly with plenty of water.

PACKAGING

10 litre plastic container.



CLEAN CORK

Cleaning liquid for Corkspray VIPEQ or CORK FIX particles that have dried on substrates.

APPLICATIONS

- Cleaning of dry corkspray on different substrates.
- Cleaning of tools.

CHARACTERISTICS

- Once the product has been applied, leave it for 1-5 minutes and then, rinse thoroughly with plenty of water.
- It is not convenient to apply this cleaner on paints or lacquers. Especially those that are not high-quality powder paints, or lack a final protective varnish can be faded by the application of CLEAN CORK. It is not convenient either to apply it on rubber or rubber joints.

PACKAGING

5 or 25 litre plastic container.

VIPEQ